



maxima

**STRONG IN
PERFORMANCE
SOFT ON YOUR
BUDGET**

WHOLE HOUSE FILTERS



ERIE WATER TREATMENT
Bannerlaan 83E,
B-2280 Grobbendonk - Belgium
T +32 (0)14 28 51 71
infobelgium@eriewatertreatment.com
WWW.ERIE-MAXIMA.COM

MEMBERSHIPS



CERTIFICATIONS



TECHNICAL SPECIFICATIONS

MODEL	MAX-WHF-		
Filter media (Ltr)	12	26	44
Operating pressure min/max (bar)	2,0/8,3		
Operating temperature min/max (°C)	2/48		
Electrical connection (V/Hz)	230/50(1)		
Max. power consumption (VA)	8		
Hydraulic connection inlet/outlet	1" BSP Male		
Hydraulic connection drain	13 mm hose barb		
Pressure tank	10x18	10x35	10x54

⁽¹⁾ Supplied with 24V transformer

PERFORMANCES @3 BAR OPERATING PRESSURE⁽²⁾

MODEL	MAX-WHF-		
Filter media (Ltr)	12	26	44
Service flow rate @1 bar (m ³ /hr) ⁽³⁾	3,6	3,4	3,2
Recomm. max. service flow (m ³ /hr) ⁽⁴⁾	1,0	1,2	1,4
Rinse water usage per regeneration (Ltr)	132	132	132
Backwash flow rate (ltr/min)	19	19	19

⁽²⁾ Indicative numbers, performances depending on operating conditions and water quality

⁽³⁾ Based on clean filter bed operation

⁽⁴⁾ Flow rate at which filtration process is still executed adequately, higher (up to x2) intermittent flow rates are possible

DIMENSIONS

MODEL	MAX-WHF-		
Filter media (Ltr)	12	26	44
Width (mm) (W)	264	264	264
Depth (mm) (D)	282	282	282
Depth, incl. factory bypass (mm) (D)	371	371	371
Height (mm) (H)	629	1.065	1.554

FEATURES & BENEFITS

- Improve taste, color and odor of the water
- Filter out any particles larger than 40µm
- Fully automatic controller with microprocessor
- Easy programming